



535 East South Frontage Road, Bolingbrook, IL 60440



NJPA CONTRACT 081716-PMC

Date: 5/11/2021

To: Village of Romeoville
615 Anderson Dr
Romeoville, IL 60446
Mike Braasch



Dear Mike,

JX Peterbilt - is pleased to present a price quotation for (1) New 2022 Peterbilt Model 348 cab and chassis with the enclosed specifications.

**Peterbilt Cab & Chassis
All as per attached specifications**

2022 Peterbilt 348 with enclose specifications	\$92,111.21
Doc Fees/title fees	Included
Heated windshield	800.00
Warranty: Eng & AFT 5yr/100 (-1800 credit from JX)	\$390.00
Total	\$93,301.21

Quote includes early chassis payoff

Option:
Heated windshield wipers ----- \$800.00

Sincerely,

Tor Michael William Larkin | Fleet Account Manager
JX Truck Center - Bolingbrook | Elmhurst | Wadsworth
Office: 630-516-3560 ext 3434 Cell: 224-200-2483
www.JXE.com | **Your Partner for the Long Haul!**

535 E. South Frontage Rd, Bolingbrook, IL 60440
Business 708-889-4886 Fax 708-889-4670

Visit us at
www.JXE.com



Peterbilt Illinois-Joliet (P128)
535 East S. Frontage Rd
Bolingbrook, Illinois 60440

Stock

Tor Larkin
Cell Phone:
Office Phone: 630-972-2720
Email: tlarkin@jxe.com

Stock Order

Vehicle Summary

	Unit		Chassis	
Model:		Model 348	Fr Axle Load (lbs):	20000
Type:		Full Truck	Rr Axle Load (lbs):	23000
Description 1:	VILLAGE OF ROMEOVILLE		G.C.W. (lbs):	43000
Description 2:	SINGLE AXLE - PINK			
	Application		Road Conditions:	
Intended Serv.:		Snowplow	Class A (Highway)	100
Commodity:		Other Commodity	Class B (Hwy/Mtn)	0
			Class C (Off-Hwy)	0
	Body		Class D (Off-Road)	0
Type:		End Dump	Maximum Grade:	6
Length (ft):		10	Wheelbase (in):	155
Height (ft):		8.5	Overhang (in):	64
Max Laden Weight (lbs):		1000	Fr Axle to BOC (in):	69.8
	Trailer		Cab to Axle (in):	85.2
No. of Trailer Axles:		0	Cab to EOF (in):	149.2
Type:			Overall Comb. Length (in):	257.2
Length (ft):		0		
Height (ft):		0	Special Req.	
Kingpin Inset (in):		0		
Corner Radius (in):		0		
	Restrictions			
Length (ft):		65		
Width (in):		102		
Height (ft):		13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	Weight
Base Model			
0003481	S	Model 348 The Model 348 was designed to exceed the rigid demands of Class 7 and Class 8 specialty application markets that require rugged durability and a wide range of optional content. The Model 348 represents a multi-dimensional performer with a GVW from 33,000 to 66,000 lbs. and optional capacity ratings to suit almost any vocation. The 348 is also available in a specifically designed all-wheel-drive configuration. From construction and crane service to utility and delivery services in both Class 7 and Class 8 markets, the 348 is in a class by itself.	10,610
0091200	S	Other Commodity	0
0093150	O	Snowplow Truck which is configured for mounting a snowplow to the front. May also have dump or other body.	0
0095170	O	End Dump	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0
Configuration			
0200700	S	Not Applicable Secondary Manufacturer	0
Frame & Equipment			
0514000	O	10-3/4" Steel Rails To 354" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	312
0611330	O	Zinc Coated Anti Corrosion Treated Frame Rails Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.	0
0612230	O	Custom Wheelbase or Overhang Engineering approval may be required.	0
0613090	S	Three-Piece Crossmembers	0
0620580	O	27.8in Bumper Extension without Adapter Includes Stationary Grille. Requires FEPTO Bumper.	75
0644090	S	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	0
0651090	S	Omit Rear Mudflaps and Hangers	0
Front Axle & Equipment			
1012200	O	Meritor MFS20 20,000 lb, 3.74 in Drop	180

Price Level: July 1, 2020
Deal: VILLAGE OF ROMEVILLE
Printed On 5/18/2021 12:46:37 PM

Date: May 18, 2021
Quote Number: QUO-762399-F8V7P0



Sales Code	Std/ Opt	Description	Weight
		Axle is designed for applications with a gross axle weight rating (GAWR) of 20,000 pounds. Axle includes special low-friction bushings, double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service. Combination of Meritor Easy Steer king pin bushings, computer-designed and optimized I-beam construction and stiff axle assembly delivering a tight turning radius, superior vehicle control and longer tire life.	
1114030	O	Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks.	119
1243050	O	Power Steering Sheppard HD94 Dual For use with 16,000 to 20,000 lb. axle ratings.	80
1250250	O	Power Steering Reservoir Frame Mounted w/Cooler A power steering cooler helps reduce the heat of the power steering fluid. This is commonly used with systems that may experience more stress from towing or off-road driving.	2
1354855	O	PHP10 Iron PreSet Hubs-Air Disc	0
1380290	O	Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	30
1380470	O	Meritor Wide Track IPO Standard, Front Axle Meritor wide track front axle offers greater turning radius and ease of service. MFS+ 3.5" Drop / MFS 3.74" Drop. 71in KPI IPO 69in with MFS and MFS+ axles.	15
Rear Axle & Equipment			
1513280	S	Dana Spicer S23-172, 23,000lb	0
1616300	O	PHP10 Iron PreSet PLUS Hubs	0
1660000	O	Dust Shields For Cam Brakes, Drive Axle(s)	15
1680450	O	Rear Brake Camshaft Reinforcement Rear brake camshaft reinforcement helps guard against wear and corrosion.	9
1680490	O	Gusseted Cam Brackets, Drive Axle(s)	2
1680500	S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0
1680795	O	Diff Lock, Single Drive Axle with Speed Interlock	30
1680950	S	Stability System Not Selected Or Not Available	0
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0

Price Level: July 1, 2020
 Deal: VILLAGE OF ROMEOVILLE
 Printed On: 5/18/2021 12:46:37 PM

Date: May 18, 2021
 Quote Number: QUO-762399-F8V7P0



Sales Code	Std/ Opt	Description	Weight
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0
1686348	S	Single Drive Axle (Model 348)	0
1687010	S	Bendix Air Cam Rear Drum Brakes 16.5x7 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0
1706140	O	Ratio 6.14 Rear Axle	0
1816090	O	Reyco 102CC 23,000 lb Single Drive	-155
Engine & Equipment			
2074407	O	PACCAR PX-9 330@2000 GOV@2200 1000@1200 Productivity (2021 Emissions) N21350 C121 64....Maximum Accelerator Pedal Ve N21370 C128 64....Maximum Cruise Speed (P059) N21460 C132 1400..Max PTO Speed (P046) N21520 C133 5.....Timer Setting (P030) N21610 C188 40....Low Ambient Temperature Thre N21620 C189 60....Intermediate Ambient Tempera N21630 C190 80....High Ambient Temperature Thr N21550 C206 100...Engine Load Threshold (P516) N21340 C209 120...Hard Maximum Speed Limit (P1 N21510 C225 YES...Enable Idle Shutdown Park Br N21450 C231 NO....Gear Down Protection (P026) N21570 C233 NO....Idle Shutdown Manual Overrul N21440 C234 NO....Engine Protection Shutdown (N21480 C238 NO....Auto Engine Brake in Cruise N21470 C239 NO....Cruise Control Auto Resume (N21430 C333 0.....Reserve Speed Limit Offset (N21410 C334 0.....Maximum Cycle Distance (N202 N21590 C382 YES...Enable Hot Ambient Automatic N21500 C395 0.....Expiration Distance (N209) N21530 C396 YES...Enable Impending Shutdown Wa N21540 C397 60....Timer For Impending Shutdown N21320 C399 120...Standard Maximum Speed Limit N21400 C400 252...Reserve Speed Function Reset N21420 C401 10....Maximum Active Distance (N20 N21330 C402 0.....Expiration Distance (N207)	0
2091305	O	Engine Idle Shutdown Timer Enabled	0

Price Level: July 1, 2020
Deal: VILLAGE OF ROMEOVILLE
Printed On: 5/18/2021 12:46:37 PM

Date: May 18, 2021
Quote Number: QUO-762399-F8V7P0



Sales Code	Std/ Opt	Description	Weight
2091315	O	Enable EIST Ambient Temp Override	0
2091372		Eff EIST NA Expiration Miles	0
2091640		Effective VSL Setting NA	0
2092013	O	Typical Operating Speed 60 MPH	0
2092032	O	Powertrain Optimized for Performance Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0
2140010	O	Belly Pan	35
2140200	S	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0
2521090	O	Immersion Type Block Heater 110-120V Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	2
2522110	S	PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0
2535040	O	3 Optima DT31T Batteries 2700 CCA Threaded Stud type terminal. AGM (Absorbent Glass Material). Stranded copper battery cables are double aught (00) or larger to reduce resistance.	55
2539410	O	Battery Jumper Terminal Mounted Under Hood LH Frame Rail. Not available with PX-7 engines.	4
2621000	O	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	0
2723210	S	18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0
2921160	S	Spin-On Fuel/Water Separator	0
2921210	S	No Fluid Heat Option for Fuel Filter	0

Price Level: July 1, 2020
Deal: VILLAGE OF ROMEVILLE
Printed On: 5/18/2021 12:46:37 PM

Date: May 18, 2021
Quote Number: QUO-762399-F8V7P0



Sales Code	Std/ Opt	Description	Weight
2921320	O	12V Heat for Fuel Filter Fuel filter heaters help ensure a seamless flow of diesel from the tank to the combustion chamber. Eliminating any possibility of moisture freezing within the fuel filter while simultaneously increasing the fuel temperature for atomization within the engine.	0
3010400	O	Engine Protection Shutdown w/ Label Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0
3211120	S	Radial Seal, Dry Type Air Cleaner, Frontal Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0
3365270	O	Exhaust Single RH Side of Cab DPF/SCR right-hand Under Cab.	29
3381770	O	Curved Tip Standpipe(s)	0
3387610	O	18" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	-2
Transmission & Equipment			
4052110	O	Allison 3000 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, Mobil Delvac Automatic Transmission Fluid, and Water-Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65. Reverse ratios: DR-(5.03).	195
4210080	S	1710 HD Driveline, 1 Midship Bearing	0
4250650	O	LH PTO Access Dipstick Tube Routing, Allison Trans	0
4252890	O	Allison FuelSense 2.0 Not Desired	0
4252950	O	Omit Allison Neutral At Stop	0

Price Level: July 1, 2020
 Deal: VILLAGE OF ROMEOVILLE
 Printed On: 5/18/2021 12:46:37 PM

Date: May 18, 2021
 Quote Number: QUO-762399-F8V7P0



Sales Code	Std/ Opt	Description	Weight
4256640	O	Allison 6-Speed Configuration, Close Ratio Gears 3000 Series Transmissions.	0
4256980	O	Seat Mounted Lever Shifter	0
Air & Trailer Equipment			
4510190	S	Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	0
4520420	O	Pull Cords All Air Tanks	0
4540420	S	Nylon Chassis Hose	0
4543340	O	Aluminum Painted Air Tanks All air tanks are aluminum with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	-45
4611730	O	7-Way Electric Harness, Socket Mounted EOF	11
4611930	O	Body Connections 5' BOC Junction box contains light and power circuits for body connections located 5' from back-of-cab	4
Tires & Wheels			
5064010	O	FF: BR 20ply 315/80R22.5 M870 Efficiency Rating: Fair Diameter= 42.8 inches; SLR= 19.9 inches The Bridgestone M870 is a high scrub All-Position Radial tire designed specifically for urban waste collection.	86
5169310	U	RR: BR 16ply 11R22.5 M799	0
5190004	O	Code-rear Tire Qty 04	0
5220520	O	FF: Alcoa 89U637 22.5 X 9.00 High Polish Aluminum, Ultra ONE technology that saves more than 50 lbs. versus a comparable steel wheel. Built for refuse, logging, mining and other heavy haul applications that demand a tough wheel. Each wheel offers a 10,000 lbs. load rating.	-36
5320410	O	RR: Alcoa 885657 22.5X8.25 High Polish Aluminum wheel severe service.	-68
5390004	O	Code-rear Rim Qty 04	0

Price Level: July 1, 2020
Deal: VILLAGE OF ROMEVILLE
Printed On: 5/18/2021 12:46:37 PM

Date: May 18, 2021
Quote Number: QUO-762399-F8V7P0



Sales Code	Std/ Opt	Description	Weight
5407640	O	FF: Mirror Polish Wheels, Outer Surface Single/tandem steer. Mirror Polish outer surface of outer wheel. Without chrome wheel nuts.	0
5407650	O	RR: Mirror Polish Wheels, Outer Surface, Single Drive without chrome wheel nuts. Mirror polish outer surface of outer wheel.	0
5410140	O	FF: Dura-Bright Finish Outer Surface of Outer Wheel, requires Polished Option	0
5410150	O	RR: Dura-Bright Finish-Single Axle Outer Surface of Outer Wheel, requires Polished Option.	0
Fuel Tanks			
5534100	O	23" Aluminum 70 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	9
5602070	O	Location LH U/C 70 Gallon	0
5650540	O	Polish (1) Non-Slip Fuel Tank Step, U/C Tank Only	0
5650810	O	Polish (1) Aluminum Fuel Tank	0
5651530	O	Raise (1) Fuel/Hydraulic Tank Approx 2-5/8" Subject to frame review	15
5652830	O	Polish All Fuel / Hydraulic Tank Straps Does not apply to rectangular DEF tank straps	0
5652880	O	DEF Tank Mounted RH BOC You have selected a Diesel Exhaust Fluid (DEF) tank mounted on the right-hand (passenger) side of the vehicle. Note, some retail fuel distributors have chosen to standardize on DEF dispensing pumps oriented to the left-hand (driver) side of the vehicle. Please verify your selection for DEF tank mounting.	0
5652990	O	DEF To Fuel Ratio 2:1 Or Greater	0
5653000	O	Polished Stainless Steel Cover For DEF Tank	0
5655019	S	DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal	0
Battery Box & Bumper			
6010780	O	Aluminum Space Saver Battery Box RH BOC Battery access from side	-84
6030540	O	Polish Battery/Tool Box(s), Aftertreatment Cab Entry complete	0
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0

Price Level: July 1, 2020
Deal: VILLAGE OF ROMEOVILLE
Printed On: 5/18/2021 12:46:37 PM

Date: May 18, 2021
Quote Number: QUO-762399-F8V7P0



Sales Code	Std/ Opt	Description	Weight
6121060	O	Steel Bumper Swept Back Painted Black, With FEPTO Two tow pin holes and step plates on top of bumper	90
Cab & Equipment			
6510110	S	Alum Cab 108in BBC Metton Hood w/Bright Crown Includes view window RH door and convex mirror over RH door.	0
6540120	O	Severe Service Cab Package #1 Includes Aluminum side skins, aluminum rear skin, steel windshield mask, steel firewall, and steel front floor sheet on all cabs, and additional reinforcement structure on the back wall of the day cab.	39
6540160	O	Thermal Insulation Package in Cab Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.	2
6800360	O	Rubber Fender Lips 2" Wide	8
6911700	S	National Driver Seat Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	0
6921700	S	National Passenger Seat Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	0
6930500	O	Drivers Armrest - RH Only	2
6930800	O	Black Seat Color IPO Standard Color	0
6939400	S	Air Ride Driver	0
6939420	S	High Back Driver	0
6939470	S	Vinyl Driver	0
6939510	S	Non-Air Ride Passenger	0
6939520	S	High Back Passenger	0
6939570	S	Vinyl Passenger	0
7001520	O	Adjustable Steering Column - Tilt/Telescope	11
7001620	S	Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0
7036120	S	Interior Gray/Black Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4)	0

Price Level: July 1, 2020
Deal: VILLAGE OF ROMEOVILLE
Printed On: 5/18/2021 12:46:37 PM

Date: May 18, 2021
Quote Number: QUO-762399-F8V7P0



Sales Code	Std/ Opt	Description	Weight
		inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.	
7210430	O	Extended Rear Window ipo Std Window-Day Cab The extended rear window protrudes two inches more than the standard conventional rear cab window. Take this into consideration when determining your loadspace.	18
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0
7230060	S	1-Piece Curved Windshield	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0
7330700	O	Peterbilt Comfort Control - Cab	6
7410040	O	Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper.	4
7561180	O	Aero Mirrors Ea Side Htd & Mtrzd 4-Way Adjustable Bright Finish with Convex	4
7564110	S	Power Package Includes power door locks and power windows.	0
7610020	O	(1) Air Horn 15" Painted Mounted under cab.	8
7722120	O	ConcertClass, AM/FM, Weatherband, 3.5 Aux	10
7725710	O	Standard Speaker Package For Cab (2) Speakers	4
7728040	O	Bluetooth Phone and Audio Requires USB Port	0
7728050	O	USB Port	0
7748140	O	CB Terminals/Wiring Mounted Under Header	0
7748500	O	CB Antenna Mounting, LH Mirror Available with Rami only on 1.9m, available without Rami on medium duty	1
7788140	O	Radio Antenna Mounted on LH Mirror Bracket	0
7850210	O	Plug-In Auto Reset Circuit Breaker in place of fuses in junction box.	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0
7900090	O	Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	13
7900270	O	Fire Extinguisher, Cab Mounted Hazmat approved UL listed/rated ABC	8
7901130	O	Backup Alarm (107 DB)	3

Price Level: July 1, 2020
 Deal: VILLAGE OF ROMEOVILLE
 Printed On: 5/18/2021 12:46:37 PM

Date: May 18, 2021
 Quote Number: QUO-762399-F8V7P0



Sales Code	Std/ Opt	Description	Weight
8011400	O	Main Transmission Oil Temperature Gauge Located in Driver Information Display	0
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall	0
8071340	O	Bright Bezel Gauges 52mm Round Gauges Only- B Panel	0
8071870	S	Main Instrumentation Panel, Graphics Display Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights with audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	0
8072560	O	(1) Additional Dash Switch With Wiring (1) additional dash switch with wiring. Spare 1 and 2 share 15 amp fuse, spares 3, 4, and 5 share 15 amp fuse. Availability subject to dash space.	0
8111110	S	Headlights Composite Fender Mounted Integral park, turn, and side marker	0
8120980	S	(5) Marker Lights, Aero LED	0
8133450	O	(2) Brackets F/O Beacon/Strobe, Roof Mounted (2) brackets for furnished by owner beacon / strobe lights roof mounted. Located above each door toward rear, includes switch and wiring.	4
8134070	O	(2) Additional Dome/Reading Lights, Ceiling Mtd	0
8140080	O	LED Stop/Turn/Tail/Backup Bracket mounted left-hand / right-hand end of frame	-7
8140850	O	Moveable EOF Crossmember For Mounting Tail Lights Square end of frame with or without end of frame crossmember	1
Paint			
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - 890524EY SUSAN G KOMEN METALLIC PINK N85500 CAB ROOF 890524EY SUSAN G KOMEN METALLIC PINK N85300 FENDER 890524EY SUSAN G KOMEN METALLIC PINK N85200 FRAME L0001EA BLACK N85400 HOOD TOP 890524EY SUSAN G KOMEN METALLIC PINK	0
8531320	O	Axalta Two Stage Effect - Metallic/Pearl Cab/Hood & Sleeper Only	0

Price Level: July 1, 2020
Deal: VILLAGE OF ROMEOVILLE
Printed On: 5/18/2021 12:46:37 PM

Date: May 18, 2021
Quote Number: QUO-762399-F8V7P0



Sales Code	Std/ Opt	Description	Weight
Shipping Destination			
8999989	O	Shipping Destination To Dealership	0
Options Not Subject To Discount			
9400091	S	Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km	0
9400094	S	PACCAR PX-9 Standard Coverage 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0
9408728	O	PACCAR Dealer Global Supply Base Surcharge	0
Miscellaneous			
9409831	O	2021 EPA Emissions Engine Warranty Only	0
9409843	O	Peterbilt Sourcewell Program Code	0
9481975	O	PACCAR 2021 PX-9 Protection Plan 1 5 Yrs/100K Mi (160,935 Km)	0
9481987	O	PACCAR 2021 PX-9 Aftertreatment Coverage (5/100) 5 Yrs/100K Mi (160,935 Km)	0

Promotions

Order Comments

Total List Price (W/O Freight & Warranty & Surcharges)	\$143,338
Marketing and Service Support Fee	\$875
Prepaid Freight	\$2,450
Total Surcharge/Options Not Subject To Discount	\$2,690
Total Weight	11,793

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this



information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: none

Final Destinations	Quantity
--------------------	----------